INVESTOR IN PEOPLE

CERTIFIED COPY OF
PRIORITY DOCUMENT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated   16 NOV 2001

Patents Form 1/77

Pate __ Act 1977
(Rule 16)

THE PATENT **The Patent**
B **Office**

2 0 MAR 2001

NEWPORT

1/77

Request for grant of a patent
*(See notes on the back of this form. You can
also get an explanatory leaflet from the Patent
Office to help you fill in this form)*

2 0 MAR 2001

The Patent Office
Cardiff Road
Newport
Gwent NP10 8QQ

---

1. Your reference

PHGB 010038

---

2. Patent application number
   (The Patent Office will fill in this part)

0106842.8

20MAR01 E615098-3 D02879
P01/7700 0.00-0106842.8

---

3. Full name, address and postcode of the or of
   each applicant *(underline all surnames)*

   Patents ADP Number *(if you know it)*

   If the applicant is a corporate body, give the
   country/state of its incorporation

KONINKLIJKE PHILIPS ELECTRONICS N.V.
GROENEWOUDSEWEG 1
5621 BA EINDHOVEN
THE NETHERLANDS

07419294001

THE NETHERLANDS

---

4. Title of the invention

BEACON INFRASTRUCTURE

---

5. Name of your agent *(if you have one)*
   "Address for service" in the United Kingdom
   to which all correspondence should be sent
   (including the postcode)

   Patents ADP number *(if you know it)*

ANDREW GORDON WHITE
Philips Corporate Intellectual Property
Cross Oak Lane
Redhill
Surrey
RH1 5HA

07133473002

---

6. If you are declaring priority from one or more
   earlier patent applications, give the country
   and the date of filing of the or of each of these
   earlier applications and *(if you know it)* the or
   each application number

Country	Priority Application number *(if you know it)*	Date of filing *(day/month/year)*

---

7. If this application is divided or otherwise
   derived from an earlier UK application, give
   the number and the filing date of the earlier
   application

Number of earlier application	Date of filing *(day/month/year)*

---

8. Is a statement of inventorship and of right to
   grant of a patent required in support of this
   request? *(Answer "Yes" if:*
   a) *any applicant named in part 3 is not an inventor, or*
   b) *there is an inventor who is not named as an
      applicant, or*
   c) *any named applicant is a corporate body.*
   See note (d))

YES

Patents form 1/77

9. Enter the number of sheets for any of the following
    items you are filing with this form.
    Do not count copies of the same document.

Continuation sheets of this form

Description	8
Claims(s)	1
Abstract	1
Drawings	1

10. If you are also filing any of the following,
    state how many against each item:

Priority Documents

Translations of priority documents

Statement of inventorship and right

to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and

search (*Patents Form 9/77*)

Request for substantive examination

(*Patents Form 10/77*)

Any other documents

(*Please specify*)

11.   I/We request the grant of a patent on the basis of this application.

Signature   Date 17-03-01

12. Name and daytime telephone number of
    person to contact in the United Kingdom   01293 815438   (A. G. WHITE)

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

a) *If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*

b) *Write your answers in capital letters using black ink or you may type them.*

c) *If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*

d) *If you have answered "Yes" Patents Form 7/77 will need to be filed.*

e) *Once you have filled in the form you must remember to sign and date it.*

f) *For details of the fee and ways to pay please contact the Patent Office.*

DESCRIPTION

BEACON INFRASTRUCTURE

5   The present invention relates to mobile communications devices, such as telephones and suitably equipped personal digital assistants (PDA's), and to infrastructure systems and protocols for use with the same.

Recent years have seen a great increase in subscribers world-wide to
10   mobile telephone networks and, through advances in technology and the addition of functionalities, cellular telephones have become personal, trusted devices. A result of this is that a mobile information society is developing, with personalised and localised services becoming increasingly more important. Such "Context-Aware" (CA) mobile telephones are used with low power, short
15   range base stations in places like shopping malls to provide location-specific information. This information might include local maps, information on nearby shops and restaurants and so on. The user's CA terminal may be equipped to filter the information received according to pre-stored user preferences and the user is only alerted if an item of data of particular interest has been received.

20   Commonly-assigned United Kingdom patent application 0020099.8 filed 15th August 2000, describes a CA terminal and puts forward the concept of broadcasting data before a connection is made according to Bluetooth protocols. It exploits the Bluetooth Inquiry phase by extending the very short ID packet sent out during this mode and using the extra space thus gained to
25   carry a small amount of information. This information can be Bluetooth system related data or one-way application data. This scheme has the potentially useful feature of being backwards-compatible with legacy Bluetooth devices that are not able to understand this extra field.

30   In accordance with the present invention there is provided a communications system as defined in the attached claims and in the following description.

The CA concept is about using a mobile handset to received special pushed messages from publicly located RF beacons. This proposal takes this idea further by suggesting a hierarchical arrangement of beacons which operate together in a co-ordinated system. A number of beacons are collected together to form a "Master Aura", within which services of a particular type are available from the operator owning the beacons. Some of the beacons are given the task of acting as "Initialisers". These special beacons are the first point of contact for handsets entering the Master Aura. They can receive identity and profile information from the handset, and pass this information on to initialise the other beacons in the Aura. Additionally, they may prime the handset with special sound files or other content relating to the user alerts that the handset may generate. By use of this procedure, whenever a handset moves near a beacon and receives a pushed message from it, it will already hold the appropriate resources to generate a specialised alert. This saves time and removes the need for duplex communication between a handset and a beacon. A further invention allows pre-load from the initialiser of interaction forms or scripts. If a user decides to follow up an alert and requests a WAP connection, the lengthy connection time is disguised by presented the user with the interaction forms.

Further features and advantages of the present invention will become apparent from reading of the following description of preferred embodiments of the present invention, given by way of example only, and with reference to the accompanying drawing, Figure 1, which is a schematic representation of an arrangement of beacons.

Many services and applications proposed for Context Aware (CA) support services that are pushed to the user. In the CA scenarios the user is wandering through a shopping mall and may receive pushed information including advertisements from shops, public transport information, personal information (friends alert), navigational information. Depending on the source of the information and the particular nature of the content, each push message can be given a class identification code. Based on that "class id" and other administrative fields in the message, the user's handset is capable of

performing filtering and sorting procedures on the data. This is done so that only messages which are considered relevant and desirable to the user in their current context are chosen for alerting to the user. The alerts themselves may take the form of sound clips, images, simple text or more complex modes such as handset vibration.

A problem with the CA concept is that it requires very low system latencies and the efficient processing of large numbers of messages. This invention solves some problems related to processing pushed messages in complex networks of beacons. Consider the arrangement of beacons in Figure 1.

Each beacon is represented by a dot, with the enclosing circle representing the range (or "Sub Aura") within which radio communication to a handset is possible. The beacon are arranged in two groups or "Master Auras", where each Master Aura represents a co-ordinated system providing a particular range of CA services and information. Our commonly-assigned United Kingdom patent application number 0020101.2, entitled "An Efficient Method for Delivering Services over Beacons", suggests novel arrangements of beacon devices. In that application, some beacons are "inquirers" which have the task of discovering handsets, and other beacons are interactors, which are responsible for the actual transmission of pushed messages. That arrangement is useful for speeding up the time for any given handset to form a connection to a beacon and receive information. The particular problem addressed by this application is related to the demands on a handset when it processes the information in a pushed message, with or without the above mentioned faster connection time modification.

It is important that the initial alert to the user is as appropriate as possible to the contents of the message. Any unnecessary ambiguity in the alert may distract the user, and cause them to waste time checking information that should have been alerted as of low priority. This would be very damaging to the user's perception of a service which must have low demands on the user's time if it is to be accepted. To this end a different sound can be related to each individual alert. This sound may be obtained from the nearest beacon

following reception of a pushed message. However, the time for this procedure could lead to an unacceptable delay, and an excessive load on an individual beacon. This problem is magnified if the alert relating to a particular message has either a number of variants, perhaps representing different priorities, or a

5   number of components, perhaps an image as well as a sound.

The proposed solution to the problem is to organise beacons into groups of a number of beacons, each of which is co-ordinated as a single system for delivery of the messages of a particular operator. The current idea is distinguished in that the operator will select one or more of the beacons in a

10   Master Aura to operate as "Initialiser" beacons. The Initialisers have the task of preparing a handset for interaction with any of the other beacons in the Aura. This could include any the following procedures:

Audio Alert Pre-load

Pre-load from the Initialiser beacon of the sound files which the handset

15   should use for alerting the user to messages within the current Master Aura. This reduces the transmission overhead on individual beacon interactions, and means that they will be available for use immediately. A set of sound would be preloaded, maybe relating to different priorities of the same message (one sound for "urgent" another for "neutral"). Another ordering would have a

20   different sound available for a particular class of alert (one sound relating to messages in Sub-Aura A, another for Sub-Aura B).

It could be appropriate for the Initialiser beacons to be located where first contact with handsets is expected, probably by the entrance or stairs leading to a new Master Aura. Each handset entering the Master Aura will now

25   be "captured" and fully prepared for generating alerts whenever appropriate from that point onwards. Alternatively, "Initialiser" may just refer to an operating mode of a beacon, which any beacon in a Master Aura may switch to as required. Some kind of expiration lifetime will be necessary, so that resources allocated to the sound files can be freed when they are unlikely to

30   be of further use (for example, a few minutes after the last contact with a beacon in a Master-Aura).

The audio alert pre-load idea is of greatest use for more advanced implementations of beacon networks which use broadcasting of pushed messages.

Message Pre-filter

5   Now that there is a hierarchy of beacons, with Master-Auras controlling Sub-Auras, there is the potential for message pre-filtering. With this concept, an Initialiser learns of the identity of a handset during its Initialisation communications. This identity can be passed on to all Sub-Aura beacons, along with some basic profile information downloaded from the handset.

10   Individual beacons will then be able to filter potential messages so that only those which are relevant to the user's profile are transmitted. (Of course, this does not preclude further filtering on the handset side after reception of a pushed message).

Pre-load for Data Retrieval from Cellular Link

15   Another benefit of Initialisers can be found when a user decides to ask for more content relating to a message from a particular alert. At this point, the user gives the handset an indication that more information is required, possibly by a simple button press. This leads to the creation of an external cellular data connection, which is used to access relevant databases or web pages that can

20   service the information request. The process of creating a data connection can take many seconds, perhaps 30 seconds for a normal WAP connection over GSM. This period of time is far too long for a user to endure without activity. However, the Initialiser scheme could be used to preload some content to the handset which can be displayed during the connection procedure. With

25   appropriate planning, this content may even include user interaction, such as a WML menu for specifying more accurately the details of the information request. After 30s, the connection will have been made and these additional parameters from the user can be passed to the data provider. By having a task to perform, the user may not even have been aware of the delay.

30   One example embodiment is illustrated in Figure 1. Consider the arrangement of two Master-Auras as described above. Master Aura B in this case relates to a particular department store, and Master Aura A relates to

some unrelated location in which the handset is initially located. The handset moves along the path from A-B-C. At point A, it has no knowledge of the Shopping Centre Aura. As it reaches B, it comes into contact with the Initialiser beacon of the Shopping Centre. It passes its identity to that beacon, and some simple profile information. In return, it receives a set of three sound files, one for each of the other Sub Aura beacons. It also obtains a WML menu appropriate to a current promotion happening in the store.

On moving to C, the Sub Aura beacon detects the presence of the handset. This beacon, located perhaps in the toys department, uses the profile information it has received about the user (transferred from the initialiser) to design an appropriate push message. This is transmitted to the handset, and in this example offers the user a special offer on some computer games software. The handset decides that this class of message is appropriate for alerting to the user, and plays the relevant sound file that has been stored since contact with the initialiser beacon. The user decides that more information is desirable, and confirms this with a button push on the handset. At this point, a WAP connection is requested. During the connection period, the user fills in some details on a WML form which is presented from the handsets memory. Again, that form was stored since contact with the initialiser beacon. When the WAP connection is available, the additional parameters are passed in the information request to an appropriate URL. For the example, the added details may relate to the particular type of game the user wishes to buy, and how much they are willing to spend on this occasion.

This invention can be used in systems providing location aware services, such as could be found in places like shopping malls, airports, stations, conference centres, museums and sports venues.

In another example of the CA arrangement, the split beacon idea divides the phases of inquiry and interaction across different radios to speed up the inquiry process. The inquirer discovers a rolling list of valid Bluetooth handset device addresses, the list being passed on to the interactors for immediate data exchange. This list can be large: tens or even hundreds of

discovered devices passing a fixed inquirer eg at an entrance gate to an installed environment of beacons.

An interactor radio is thus given the job of polling those Bluetooth addresses on its list and guaranteeing the transmission of some data to those

5   handsets. Unfortunately, this involves paging the devices in turn before data transmission. The simple paging mechanism itself can take about two seconds per device, and although there are some Bluetooth Special Interest Group proposals to speed paging up, it may still be of the order of a second per device. Therefore, in very crowded places of interaction, there is still a load

10   problem . If paging takes one second, then only about eight devices can guarantee to be serviced (less with any significant data exchange per device) in the time it takes a walking user to pass out of the 10 metre range of the interactor radio (in time terms 5-8 seconds).

The particular feature is to cluster a number of interactor radios together

15   in the same place and partition the allocation of the complete list of discovered Bluetooth handset addresses across the interactor radios. For example, the first radio handles first 5 device addresses, a second radio handles the next set, etc. So the cluster of radios might consist of 1 inquirer and 10 interactors together, to handle simultaneous interaction with 80 people in a 10 metre zone

20   such as a train station concourse. According to the expected peak crowd numbers expected, then the number of radios required in a place can be estimated. .

A further extension is possible when there is a geographical hierarchy of beacons, with some interactors serving non-overlapping zones, for example

25   interactor number 5 does not overlap with the zone of interactor number 11. Now, some dynamic screening of the device address lists of the interactors can be performed. Any Bluetooth interaction with a device returns to the interactor radio (with v1.1 Bluetooth, not of course with connectionless-broadcasting) the handset device's ID, Bluetooth address with which it had that

30   exchange. Knowing the layout of beacon coverage, it is therefore possible to say that if that handset is in range of interactor 5, then interactor 11 does not have to try to poll that Bluetooth address, and so on. The device address lists

ABSTRACT

BEACON INFRASTRUCTURE

5   A communications system comprising a plurality of beacons interconnected to
form master auras within which services of a particular type are available from
the operator owning the beacons.

(Figure 1)

Master Aura A

Sub Aura 1

Sub Aura 2

Sub Aura 3

A

Shopping Centre

Master Aura B

Sub Aura 2

Sub Aura 4

Sub Aura 1

B

C

Sub Aura 3

FIG. 1

PHGB 010038